- 1. (currently amended). A container having a consumable liquid having an interior wall and further having a drinking straw housed therein, wherein the straw is in at least a partially collapsed position within the container, and wherein the straw is intended to be straightened out and to extend above the container once the container is uncapped or otherwise opened, the improvement comprising the straw having two spaced-apart corrugated sections, one corrugated section the straw having an end anchored to the interior wall, the other portion formed integrally with the container, one corrugated section being disposed intermediately along the length of the straw, each corrugated section having a non-uniform cross-section including respective different portions which are substantially diametrically opposite to one another, such that the straw will tend to bend in a desired direction when partially collapsed within the container, and such that the straw will substantially straighten out and extend above the container when the container is uncapped or otherwise opened, the straw being devoid of a float.
- 2. (previously amended) The improvement of claim 1, wherein each corrugated section of the straw includes a wall having a differential wall thickness.
 - 3. (withdrawn) The improvement of claim 2, wherein, the wall is cone shaped.
 - 4. (original) The improvement of claim 2, wherein the wall is disk shaped.
- 5. (previously amended) The improvement of claim 1, wherein one side of the cross-section of each corrugated section of the straw is provided with a stiffener.
 - 6. (original) The improvement of claim 5, wherein the stiffener is hollowed out.
- 7. (previously amended) The improvement of claim 1, wherein one of the corrugated sections has a cross-section which is opposite to the cross-section of the other corrugated section,

such that the corrugated sections of the straw tend to bend into a substantially "S" shape and direction.

- 8. (withdrawn) The improvement of claim 1, wherein the corrugated section is a substantial portion of the length of the straw.
- 9. (original) The improvement of claim 1, wherein the straw is made as one piece with the container.
- 10. (withdrawn) The improvement of claim 1, wherein the straw has an end portion which is anchored in a sleeve within the container.
- straw housed therein, wherein the straw is in at least a partially collapsed position within the container, and wherein the straw is intended to be straightened out and to extend above the container once the container is uncapped or otherwise opened, the improvement comprising the straw having at least one pair of spaced-apart corrugated sections intermediately along the length of the straw, the corrugated sections each having a non-uniform cross-section including diametrically-opposite portions having different wall thicknesses, respectively, and one of the corrugated sections being a mirror image of the other corrugated section, such that the corrugated sections of the straw will tend to bend into a desired "S" shape and direction collapsed with the container, and such that the straw will substantially straighten out and extend above the container when the container is uncapped or otherwise opened.

- straw housed therein, wherein the straw is in at least a partially collapsed position within the container, and wherein the straw is intended to be straightened out and to extend above the container once the container is uncapped or otherwise opened, the improvement comprising the straw having a corrugated section along a substantial portion of the length of the straw, the corrugated section having a non-uniform cross-section including different portions which are substantially diametrically opposite to one another, and which have different wall thicknesses; respectively, such that the straw will tend to bend in a desired direction when partially collapsed within the container; and such that the straw, due to its built-in resiliency, will substantially straighten out and extend above the container when the container is uncapped or otherwise opened.
- drinking straw housed therein, wherein the straw is in at least a partially collapsed position within the container, and wherein the straw is intended to be straightened out and to extend above the container once the container is uncapped or otherwise opened, the improvement comprising the straw having at least one section having a non-uniform cross-section including different portions which are substantially diametrically opposite to one another, a stiffener such that the straw has a built-in resiliency and will substantially straighten out and extend above the container when the container is uncapped or otherwise opened, and the straw having an end portion substantially anchored within the container, thereby precluding complete removal of the straw out of the container, the at least one section having a plurality of concave portions such that the straw bends at the concave portion, the straw being devoid of a float.

- 14. (previously presented) The improvement of claim 13, wherein the at least one section of the straw is corrugated.
- 15. (withdrawn) The improvement of claim 14, wherein the corrugations are cone shaped.
- 16. (currently amended) The improvement of claim 14, wherein the corrugations are corrugation is disk shaped.
- 17. (currently amended) The improvement of claim 14 wherein the end of the at least one corrugated section is directly connected to the interior wall of straw is formed integrally with the container.